



CLASSIC SERIES A3S4


15 PSI STEAM / 30, 40, 80, 150 PSI WATER • 83-87% EFFICIENCY • 4 Sq Ft FIRESIDE HEATING SURFACE/BHP
 HORIZONTAL FIRETUBE BOILER MANUFACTURED BY ALDRICH COMPANY FOR OVER 30 YEARS
 HIGH EFFICIENCY • HEAVY DUTY CONSTRUCTION • THREE PASS SCOTCH BOX DESIGN • ASME SECTION IV
 MODELS UP TO 125 HP FIT THROUGH 36" DOORWAY • A3S4 SERIES OFFERS BURNER VERSATILITY

BOILER RATINGS & DIMENSIONS

MODEL: A3S4-	10	15	20	25	30	40	50	60	70	80	90	105	110	120	125	135	150	175	200	225	250
Gas Input (MBH)	399	600	800	1,000	1,200	1,610	2,010	2,410	2,820	3,220	3,620	4,240	4,430	4,865	5,040	5,450	6,050	7,100	8,100	9,100	10,100
Oil Input (GPH)	2.9	4.3	5.7	7.1	8.6	11.5	14.4	17.2	20.1	23.0	25.9	30.3	31.6	34.8	36.0	38.9	43.2	50.7	57.9	65.0	72.1
Output (MBH)	330	500	670	835	1,000	1,340	1,675	2,010	2,345	2,680	3,015	3,520	3,680	4,040	4,184	4,520	5,020	5,860	6,695	7,532	8,369
Output (Horsepower)	10	15	20	25	30	40	50	60	70	80	90	105	110	120	125	135	150	175	200	225	250
Htg Surf. FS (Sq Ft)	48	60	87	102	125	162	200	242	285	325	359	425	458	480	508	542	602	710	834	908	1,001
Furnace Vol (Cu Ft)	4.5	4.5	6.1	6.1	7.7	9.3	13.6	15.8	20.3	20.3	23.2	26.0	28.1	30.2	30.2	38.0	43.3	56.0	66.3	72.0	77.6
Water Cap. (Gal, NWL)	91	89	116	111	138	160	206	237	282	270	312	344	360	406	402	425	482	590	694	740	787
Dry Weight (LBS)	1,725	1,750	2,050	2,150	2,500	2,825	3,500	4,000	4,650	4,800	5,200	5,675	5,950	6,250	6,350	6,550	7,250	8,800	10,750	12,500	14,250
A Width	28	28	28	28	28	28	**35¼	**35¼	**35¼	**35¼	**35¼	**35¼	**35¼	**35¼	**35¼	42	42	42	42	42	42
B Width With Trim	40	40	40	40	40	40	46	46	46	46	46	46	46	46	46	54	54	54	54	54	54
C Length of Skid	29¼	29¼	39	39	48¼	58½	58½	68¼	68¼	68¼	78	87¼	92¼	96¼	102	78	94	111½	131	143½	156
D Overall Length	64	64	76	76	86	96	112	121	123	128	138	154	156	158	164	142	158	181	200	212	225
E Supply Height	64	64	64	64	64	64	72	72	78	78	78	78	78	78	78	78	90	90	90	90	90
F Height With Trim	72	72	72	72	72	72	79	79	86	86	86	86	86	86	86	86	94¼	94¼	94¼	94¼	94¼
G Stack Dia., O.D.	6	6	8	8	8	8	10	10	12	12	12	12	12	12	12	16	18	20	20	20	20
H Stack Height	50	50	50	50	50	50	54	54	61	61	61	61	61	61	61	70	70	70	70	70	70
I Burner Port Height	18	18	18	18	18	18	19½	19½	19½	19½	19½	19½	19½	19½	19½	23¼	23¼	23¼	23¼	23¼	23¼
J Supply Size (*Flg)	3	3	3	3	*4	*4	*6	*6	*6	*6	*6	*8	*8	*8	*8	*8	*10	*10	*10	*10	*10
K Supply Location	14¼	14¼	19½	19½	24¼	29	29	34	34	34	39	44	46	48	51	39	47	56	65½	72	78
L Return Size (NPT)	2	2	2	3	3	3	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
M Return Height	8½	8½	8½	8½	8½	8½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½	10½
N BD/Drain Size	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½	1½
O Tube Pull Space	30	30	40	40	50	60	60	69	69	69	79	89	93	98	103	79	95	112	132	144	157

**WIDTH LISTED AT 35¼" (THIS INCLUDES THE ANGLE TRIM FOR SECURING OUTER BOILER JACKET). WIDTH WITH ANGLE TRIM REMOVED IS 34".

ALL DIMENSIONS ARE IN INCHES. DIMENSIONS SUBJECT TO CHANGE WITHOUT NOTICE. CERTIFIED DRAWING AVAILABLE UPON REQUEST. CONSULT FACTORY FOR CUSTOMIZED APPLICATIONS.



QUALITY • PERFORMANCE • EFFICIENCY • EXPERIENCE

"QUALITY PRODUCTS BY LOYAL CRAFTSMEN" STEEL BOILERS & WATER HEATERS SINCE 1936
 ALDRICH COMPANY • 341 EAST WILLIAMS ST., P.O. BOX 97, WYOMING, IL 61491 • TEL: 309-695-2311 • FAX: 309-695-5779

WWW.ALDRICHCO.COM